



Scapa 1695

Metalised Polyester Adhesive Tape

DESCRIPTION

Scapa 1695 is a 23µm coloured metalised polyester film coated with a long ageing acrylic adhesive system, with 45µm total thickness and recommended for general splicing, decorative and sealing applications.

APPLICATIONS

- Suitable for a variety of long ageing and/or temperature resistant decorative, sealing and splicing applications.
- Splicing and web defects reflective tape for sensors.
- Repairing and splicing thermal blankets and screens in the horticultural industry.
- Double glazed sealing.
- Decorative edging and reinforcing tape.

PRODUCT BENEFITS

- Service temperature: -15°C to +130°C.
- Wide continuous temperature resistance.
- Long ageing adhesive.
- High chemical, moisture and solvent resistance.
- High tensile strength.
- Good shear resistance.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Total Thickness	0.045	mm	AFERA 5006
Tensile Strength	50	N/cm	AFERA 4004
Elongation at Break	135	%	AFERA 4005
Adhesion to Steel	7.0	N/25mm	AFERA 5001

STANDARD PRESENTATIONS

- Roll Width: a) 12, 15, 19, 25, 30, 38 and 50 mm b) 25, 38 and 50 mm
- Roll Length: a) 66 metres b) 660 metres
- Packaging: a) Bags (for 12 to 30 mm) - Concertina (for 38 and 50 mm) b) Bulk in cartons
- Core: 76 mm Scapa branded cardboard core
- Colours: Silver

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.