



Scapa 4400

General Purpose u-PVC Double Sided Tape

DESCRIPTION

Scapa 4400 is a general purpose double sided tape based on a UPVC film. The tape is coated on both sides with a solvent rubber based adhesive system with an 80gr. yellow siliconised paper release liner, resulting in a total thickness of 0.10 mm. Recommended for general purpose bonding, mounting and splicing applications.

APPLICATIONS

- Show card assembly.
- Mounting dummy packs and sample cards.
- Mounting display items.
- General purpose splicing tape except for siliconised films and papers.
- Mounting sample cards.

PRODUCT BENEFITS

- Service temperature: -10°C to +70°C.
- Not recommended for direct exposure to sunlight or UV.
- High tack.
- Clean removal after use.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Total Thickness (Without Liner)	0.10	mm	AFERA 5006
Tensile Strength	150	N/25mm	ASTMD882
Liner Thickness	0.07	mm	AFERA 5006
Elongation at Break	75	%	ASTMD882
Adhesion to Steel	12	N/25mm	AFERA 5001

Version: 1

Date: 14/06/2016

Page: 1 of 2

www.scapa.com

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

STANDARD PRESENTATIONS

- Roll Width: 9, 12, 19, 25, 30, 38 and 50 mm
- Roll Length: 50 metres
- Packaging: Plastic Bags
- Core: 76 mm Scapa branded cardboard
- Colours: Transparent

Note:

Note: Other dimensions are available upon request and subject to minimum order quantities.

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the shelf life of the tape is 12 months from date of dispatch. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.