



Scapa 9130S

High Temperature Paper Masking Adhesive Tape

DESCRIPTION

Scapa 9130S is a 160µm semi crepe paper tape coated with a cured rubber/resin solvent based adhesive system, recommended for all high temperature 120°C masking applications.

APPLICATIONS

- Suitable for all industrial high temperature masking applications up to 120°C
- Premium masking tape for automotive, aircraft, bus, ship and trucks.
- Designed for use where high cure temperatures are required.
- High strength masking tape.

PRODUCT BENEFITS

- Temperature resistance: +120°C up to 30 minutes.
- Smooth and controlled unwind.
- Resistant to oven baking.
- Resistant to chemicals, lacquers and solvents.
- Non staining.
- High tensile strength.
- Good peel adhesion and shear resistance.
- Conformable.
- Clean removal.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Total Thickness	160	µm	AFERA 5006
Tensile Strength	44	N/cm	AFERA 5004
Elongation at Break	9	%	AFERA 5005
Adhesion to Steel	2.3	N/cm	AFERA 5001

STANDARD PRESENTATIONS

- Roll Width: 12, 19, 25, 38, 50 and 250mm
- Roll Length: 50 metres
- Packaging: Concertina
- Core:
- Colours: Natural

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

Scapa masking tapes are not suitable for outdoor exposure and should not be submitted to prolonged periods of sunlight, as tapes may become difficult to remove. Clean removal may also vary with surface type, lacquers, primers and paints nature and the temperature of the surface at removal. For best results, remove the tape as soon as possible after applying the paints pulling it slowly at a 90° angle with constant speed.