

tesa® 4368

Masking film with slightly creped adhesive paper tape

PRODUCT INFORMATION

Product Description

Easy Cover® 4368 Universal is a combination of an HDPE film and a slightly creped adhesive paper tape for the masking of large areas in one working step. It is resistant to water-based paints and can easily be removed after short term applications without residues. Easy Cover 4368 has been successfully tested on all standard indoor applications. It allows safe and precise fixing on even surfaces such as skirting boards, window sills, window and door frames. The embossed film avoids paint bleeding or leaking to the protected area. Easy Cover 4368 will achieve a clean paint result with straight paint edges.

Main Application

For base boards, window sills, door and window frames etc.

Technical Data

■ Backing material	slightly-creped paper	■ Elongation at break	10 %
■ Total thickness	140 µm	■ Tensile strength	38 N/cm
■ Thickness of masking coverage	10 µm	■ UV-resistance	1 weeks
■ Type of adhesive	natural rubber	■ Material of masking coverage	HDPE
■ Adhesion to steel	3.4 N/cm		

Properties

■ Suitable for sensitive surfaces	++	■ Sharp colour edge	++
■ Paint anchorage	++		

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=04368>

Page 1 of 1 / As of 06/03/14

tesa UK Ltd.

Yeomans Drive, Blakelands
Milton Keynes, Bucks MK 14 5LS
Phone: +44 (1) 908 211 333
Fax: +44 (1) 908 211 555
ukenquiry@tesa.com
www.tesa.co.uk

tesa SE
A Beiersdorf Company

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.